

Advising Professor at Tohoku Univ.	Professor Edward CIVIL
Research Advisor at Tohoku Univ.	Assoc.Prof. J. DOE
Dissertation Committee Members Name marked with "○" is the Chief Examiner	○ Professor Edward CIVIL <u>1 Prof. W. DOE</u> <u>2 Prof. L. DOE</u> <u>3 Prof. T. DOE</u> <u>4 Assoc.Prof. J. DOE</u>

Author's Profile	
Name Doboku, Koji	Date of Birth October 1, 1979
Nationality Japan	
Curriculum Vitae	
Educational Background	
From April 1, 1998 To March 26, 2002	School of Engineering, Tohoku Univ.
From April 1, 2002 To March 25, 2004	Graduate School of Engineering, Tohoku Univ. (Master's Program)
From April 1, 2011 To March 26, 2014	Graduate School of Engineering, Tohoku Univ. (Doctoral Program)
From To	
From To	
Work Experience	
From April 1, 2004 To March 20, 2010	Tohoku Construction Co.
From To	
From To	

Note: Educational background has to be filled in, starting from the date of university enrollment.

Estimate of Average Elastoplastic Moduli of
Composites and
Localized Deformation

A MASTER THESIS

SUBMITTED TO THE DEPARTMENT OF CIVIL AND ENVIRONMENTAL ENGINEERING

AND THE COMMITTEE ON GRADUATE STUDIES

OF TOHOKU UNIVERSITY

FOR THE DEGREE OF

MASTER OF ENGINEERING

KOJI DOBOKU

MARCH 2015

Copyright © 2015 by Koji DOBOKU

Professor Edward CIVIL
(Principal Advisor)

Prof. W. DOE

Prof. L. DOE

Prof. T. DOE

Assoc.Prof. J. DOE

ABSTRACT

ESTIMATE OF AVERAGE ELASTOPLASTIC MODULI OF COMPOSITES AND LOCALIZED DEFORMATION

Koji DOBOKU

The Jaumann stress rate of the Cauchy stress is usually used to represent hypoelasticity. Since this stress rate takes into account only the effect of finite rotation; i.e. spin during motion, we here examined the effects of deformation rate terms which can be included in the definitions of the stress rates. First we have shown that the Truesdell stress rate can be defined as a rate of the 2nd Piola-Kirchhoff stress with the current state as reference; i.e. an updated Lagrangian measure.

In order to compare the characteristics of the stress rates, localization of deformation was predicted by using the Truesdell stress rate and the convected stress rate, and the results were compared with those by the Jaumann stress rate of the Cauchy stress. However, in plane strain state, the predicted stresses of incipience of the localization by the Truesdell stress rate become close to the experimental critical stresses, Also, the orientations of the localized deformation obtained by the Truesdell stress rate showed consistency with those by the infinitesimal deformation theory, when the stress levels of the localization were in practical order.

In order to compare the characteristics of the stress rates, localization of deformation was predicted by using the Truesdell stress rate and the convected stress rate, and the results

were compared with those by the Jaumann stress rate of the Cauchy stress. However, in plane strain state, the predicted stresses of incipience of the localization by the Truesdell stress rate become close to the experimental critical stresses, Also, the orientations of the localized deformation obtained by the Truesdell stress rate showed consistency with those by the infinitesimal deformation theory, when the stress levels of the localization were in practical order.

ACKNOWLEDGMENT

I appreciate

Contents

1	Introduction	1
2	The averaging approach to multi-phase elastoplastic composites	3
(1)	Mori-Tanaka averaging in incremental form	3
a)	3D expression	3
(2)	Localization	4
a)	Classical approaches	4
b)	Finite deformation	4
3	Experimental approaches	6
(1)	Uniaxial case	6
a)	Infinitesimal deformation	6
4	Concluding remarks	8
	APPENDIX A Ductility	10
(1)	In the case of	10
(2)	Incremental theory	11
	REFERENCES	13

List of Tables

1	Material parameters	15
2	Experimental settings	15

List of Figures

1	First results	16
2	Second results	16

List of Photos

1	My helicopter	17
---	-------------------------	----

1 . Introduction

Analytical methods for averaging the material characteristics of composites are extremely useful in designing new materials long before carrying out either experimental trials or numerical analyses with precise models of microstructure. Among many such methods, the Mori-Tanaka approach¹⁾ is a simple one used to evaluate the average elastic and elastoplastic properties of composites²⁾. However, since the method does not take into account the mechanical interactions between many inhomogeneities, the predicted behavior, especially in the plastic states, tends to be significantly stiffer than what is observed in experiments. In order to improve its ability to predict the behavior of materials, a variety of approaches has been suggested: an explicit geometrical distribution of inhomogeneities was assumed and introduced³⁾, and secant and tangential moduli were employed to evaluate interactions approximately by Doe⁴⁾.

The Jaumann stress rate of the Cauchy stress is usually used to represent hypoelasticity. Since this stress rate takes into account only the effect of finite rotation; i.e. spin during motion, we here examined the effects of deformation rate terms which can be included in the definitions of the stress rates. First we have shown that the Truesdell stress rate can be defined as a rate of the 2nd Piola-Kirchhoff stress with the current state as reference; i.e. an updated Lagrangian measure.

In order to compare the characteristics of the stress rates, localization of deformation was predicted by using the Truesdell stress rate and the convected stress rate, and the results were compared with those by the Jaumann stress rate of the Cauchy stress. However, in plane strain state, the predicted stresses of incipience of the localization by the Truesdell

stress rate become close to the experimental critical stresses, Also, the orientations of the localized deformation obtained by the Truesdell stress rate showed consistency with those by the infinitesimal deformation theory, when the stress levels of the localization were in practical order.

The Jaumann stress rate of the Cauchy stress is usually used to represent hypoelasticity. Since this stress rate takes into account only the effect of finite rotation; i.e. spin during motion, we here examined the effects of deformation rate terms which can be included in the definitions of the stress rates. First we have shown that the Truesdell stress rate can be defined as a rate of the 2nd Piola-Kirchhoff stress with the current state as reference; i.e. an updated Lagrangian measure.

In order to compare the characteristics of the stress rates, localization of deformation was predicted by using the Truesdell stress rate and the convected stress rate, and the results were compared with those by the Jaumann stress rate of the Cauchy stress. However, in plane strain state, the predicted stresses of incipience of the localization by the Truesdell stress rate become close to the experimental critical stresses, Also, the orientations of the localized deformation obtained by the Truesdell stress rate showed consistency with those by the infinitesimal deformation theory, when the stress levels of the localization were in practical order.

2 . The averaging approach to multi-phase elastoplastic composites

(1) Mori-Tanaka averaging in incremental form

a) 3D expression

Suppose that there are $(N - 1)$ different types of ellipsoidal inhomogeneities distributed in an infinite body where the N -th phase is the matrix. Let $\dot{\sigma}$, $\dot{\varepsilon}$ and C denote the incremental stress tensor, incremental strain tensor and tangential isotropic elastic tensor, respectively. Since a virtual matrix introduced in the next section is an elastic body because, for example, the Eshelby tensor can be easily evaluated, the matrix (N -th phase) is assumed to be isotropically elastic, and the corresponding constitutive relation in rate form is expressed as

The Jaumann stress rate of the Cauchy stress is usually used to represent hypoelasticity. Since this stress rate takes into account only the effect of finite rotation; i.e. spin during motion, we here examined the effects of deformation rate terms which can be included in the definitions of the stress rates. First we have shown that the Truesdell stress rate can be defined as a rate of the 2nd Piola-Kirchhoff stress with the current state as reference; i.e. an updated Lagrangian measure.

In order to compare the characteristics of the stress rates, localization of deformation was predicted by using the Truesdell stress rate and the convected stress rate, and the results were compared with those by the Jaumann stress rate of the Cauchy stress. However, in plane strain state, the predicted stresses of incipience of the localization by the Truesdell

stress rate become close to the experimental critical stresses, Also, the orientations of the localized deformation obtained by the Truesdell stress rate showed consistency with those by the infinitesimal deformation theory, when the stress levels of the localization were in practical order.

(2) Localization

a) Classical approaches

Then, based on the Mori-Tanaka approach, an approximate average constitutive relation of the matrix can be assumed by

The Jaumann stress rate of the Cauchy stress is usually used to represent hypoelasticity. Since this stress rate takes into account only the effect of finite rotation; i.e. spin during motion, we here examined the effects of deformation rate terms which can be included in the definitions of the stress rates. First we have shown that the Truesdell stress rate can be defined as a rate of the 2nd Piola-Kirchhoff stress with the current state as reference; i.e. an updated Lagrangian measure.

In order to compare the characteristics of the stress rates, localization of deformation was predicted by using the Truesdell stress rate and the convected stress rate, and the results were compared with those by the Jaumann stress rate of the Cauchy stress. However, in plane strain state, the predicted stresses of incipience of the localization by the Truesdell stress rate become close to the experimental critical stresses, Also, the orientations of the localized deformation obtained by the Truesdell stress rate showed consistency with those by the infinitesimal deformation theory, when the stress levels of the localization were in practical order.

b) Finite deformation

The strain field of the i -th inhomogeneity must include the interaction between the particular inhomogeneity and the surrounding matrix material, and can be written as

The Jaumann stress rate of the Cauchy stress is usually used to represent hypoelasticity. Since this stress rate takes into account only the effect of finite rotation; i.e. spin during motion, we here examined the effects of deformation rate terms which can be included in the definitions of the stress rates. First we have shown that the Truesdell stress rate can be defined as a rate of the 2nd Piola-Kirchhoff stress with the current state as reference; i.e. an updated Lagrangian measure.

In order to compare the characteristics of the stress rates, localization of deformation was predicted by using the Truesdell stress rate and the convected stress rate, and the results were compared with those by the Jaumann stress rate of the Cauchy stress. However, in plane strain state, the predicted stresses of incipience of the localization by the Truesdell stress rate become close to the experimental critical stresses, Also, the orientations of the localized deformation obtained by the Truesdell stress rate showed consistency with those by the infinitesimal deformation theory, when the stress levels of the localization were in practical order.

The Jaumann stress rate of the Cauchy stress is usually used to represent hypoelasticity. Since this stress rate takes into account only the effect of finite rotation; i.e. spin during motion, we here examined the effects of deformation rate terms which can be included in the definitions of the stress rates. First we have shown that the Truesdell stress rate can be defined as a rate of the 2nd Piola-Kirchhoff stress with the current state as reference; i.e. an updated Lagrangian measure.

In order to compare the characteristics of the stress rates, localization of deformation was predicted by using the Truesdell stress rate and the convected stress rate, and the results were compared with those by the Jaumann stress rate of the Cauchy stress. However, in plane strain state, the predicted stresses of incipience of the localization by the Truesdell stress rate become close to the experimental critical stresses, Also, the orientations of the localized deformation obtained by the Truesdell stress rate showed consistency with those by the infinitesimal deformation theory, when the stress levels of the localization were in practical order.

3 . Experimental approaches

(1) Uniaxial case

a) Infinitesimal deformation

Then the equivalent inclusion method⁵⁾ allows the following expression in the i -th inhomogeneity as

The Jaumann stress rate of the Cauchy stress is usually used to represent hypoelasticity. Since this stress rate takes into account only the effect of finite rotation; i.e. spin during motion, we here examined the effects of deformation rate terms which can be included in the definitions of the stress rates. First we have shown that the Truesdell stress rate can be defined as a rate of the 2nd Piola-Kirchhoff stress with the current state as reference; i.e. an updated Lagrangian measure.

In order to compare the characteristics of the stress rates, localization of deformation was predicted by using the Truesdell stress rate and the convected stress rate, and the results were compared with those by the Jaumann stress rate of the Cauchy stress. However, in plane strain state, the predicted stresses of incipience of the localization by the Truesdell stress rate become close to the experimental critical stresses, Also, the orientations of the localized deformation obtained by the Truesdell stress rate showed consistency with those by the infinitesimal deformation theory, when the stress levels of the localization were in practical order.

The Jaumann stress rate of the Cauchy stress is usually used to represent hypoelasticity. Since this stress rate takes into account only the effect of finite rotation; i.e. spin during

motion, we here examined the effects of deformation rate terms which can be included in the definitions of the stress rates. First we have shown that the Truesdell stress rate can be defined as a rate of the 2nd Piola-Kirchhoff stress with the current state as reference; i.e. an updated Lagrangian measure.

In order to compare the characteristics of the stress rates, localization of deformation was predicted by using the Truesdell stress rate and the convected stress rate, and the results were compared with those by the Jaumann stress rate of the Cauchy stress. However, in plane strain state, the predicted stresses of incipience of the localization by the Truesdell stress rate become close to the experimental critical stresses, Also, the orientations of the localized deformation obtained by the Truesdell stress rate showed consistency with those by the infinitesimal deformation theory, when the stress levels of the localization were in practical order.

4 . Concluding remarks

The Jaumann stress rate of the Cauchy stress is usually used to represent hypoelasticity. Since this stress rate takes into account only the effect of finite rotation; i.e. spin during motion, we here examined the effects of deformation rate terms which can be included in the definitions of the stress rates. First we have shown that the Truesdell stress rate can be defined as a rate of the 2nd Piola-Kirchhoff stress with the current state as reference; i.e. an updated Lagrangian measure.

In order to compare the characteristics of the stress rates, localization of deformation was predicted by using the Truesdell stress rate and the convected stress rate, and the results were compared with those by the Jaumann stress rate of the Cauchy stress. However, in plane strain state, the predicted stresses of incipience of the localization by the Truesdell stress rate become close to the experimental critical stresses, Also, the orientations of the localized deformation obtained by the Truesdell stress rate showed consistency with those by the infinitesimal deformation theory, when the stress levels of the localization were in practical order.

The Jaumann stress rate of the Cauchy stress is usually used to represent hypoelasticity. Since this stress rate takes into account only the effect of finite rotation; i.e. spin during motion, we here examined the effects of deformation rate terms which can be included in the definitions of the stress rates. First we have shown that the Truesdell stress rate can be defined as a rate of the 2nd Piola-Kirchhoff stress with the current state as reference; i.e. an updated Lagrangian measure.

In order to compare the characteristics of the stress rates, localization of deformation

was predicted by using the Truesdell stress rate and the convected stress rate, and the results were compared with those by the Jaumann stress rate of the Cauchy stress. However, in plane strain state, the predicted stresses of incipience of the localization by the Truesdell stress rate become close to the experimental critical stresses, Also, the orientations of the localized deformation obtained by the Truesdell stress rate showed consistency with those by the infinitesimal deformation theory, when the stress levels of the localization were in practical order.

Finally, we can define the overall average incremental stress $\dot{\bar{\sigma}}$ and the corresponding incremental strain $\dot{\bar{\epsilon}}$ of the composite by simple volume averages as

APPENDIX A . Ductility

(1) In the case of ...

The Jaumann stress rate of the Cauchy stress is usually used to represent hypoelasticity. Since this stress rate takes into account only the effect of finite rotation; i.e. spin during motion, we here examined the effects of deformation rate terms which can be included in the definitions of the stress rates. First we have shown that the Truesdell stress rate can be defined as a rate of the 2nd Piola-Kirchhoff stress with the current state as reference; i.e. an updated Lagrangian measure.

In order to compare the characteristics of the stress rates, localization of deformation was predicted by using the Truesdell stress rate and the convected stress rate, and the results were compared with those by the Jaumann stress rate of the Cauchy stress. However, in plane strain state, the predicted stresses of incipience of the localization by the Truesdell stress rate become close to the experimental critical stresses, Also, the orientations of the localized deformation obtained by the Truesdell stress rate showed consistency with those by the infinitesimal deformation theory, when the stress levels of the localization were in practical order.

The Jaumann stress rate of the Cauchy stress is usually used to represent hypoelasticity. Since this stress rate takes into account only the effect of finite rotation; i.e. spin during motion, we here examined the effects of deformation rate terms which can be included in the definitions of the stress rates. First we have shown that the Truesdell stress rate can be defined as a rate of the 2nd Piola-Kirchhoff stress with the current state as reference; i.e. an

updated Lagrangian measure.

In order to compare the characteristics of the stress rates, localization of deformation was predicted by using the Truesdell stress rate and the convected stress rate, and the results were compared with those by the Jaumann stress rate of the Cauchy stress. However, in plane strain state, the predicted stresses of incipience of the localization by the Truesdell stress rate become close to the experimental critical stresses, Also, the orientations of the localized deformation obtained by the Truesdell stress rate showed consistency with those by the infinitesimal deformation theory, when the stress levels of the localization were in practical order.

The Jaumann stress rate of the Cauchy stress is usually used to represent hypoelasticity. Since this stress rate takes into account only the effect of finite rotation; i.e. spin during motion, we here examined the effects of deformation rate terms which can be included in the definitions of the stress rates. First we have shown that the Truesdell stress rate can be defined as a rate of the 2nd Piola-Kirchhoff stress with the current state as reference; i.e. an updated Lagrangian measure.

(2) Incremental theory

The Jaumann stress rate of the Cauchy stress is usually used to represent hypoelasticity. Since this stress rate takes into account only the effect of finite rotation; i.e. spin during motion, we here examined the effects of deformation rate terms which can be included in the definitions of the stress rates. First we have shown that the Truesdell stress rate can be defined as a rate of the 2nd Piola-Kirchhoff stress with the current state as reference; i.e. an updated Lagrangian measure.

In order to compare the characteristics of the stress rates, localization of deformation was predicted by using the Truesdell stress rate and the convected stress rate, and the results were compared with those by the Jaumann stress rate of the Cauchy stress. However, in plane strain state, the predicted stresses of incipience of the localization by the Truesdell

stress rate become close to the experimental critical stresses, Also, the orientations of the localized deformation obtained by the Truesdell stress rate showed consistency with those by the infinitesimal deformation theory, when the stress levels of the localization were in practical order.

The Jaumann stress rate of the Cauchy stress is usually used to represent hypoelasticity. Since this stress rate takes into account only the effect of finite rotation; i.e. spin during motion, we here examined the effects of deformation rate terms which can be included in the definitions of the stress rates. First we have shown that the Truesdell stress rate can be defined as a rate of the 2nd Piola-Kirchhoff stress with the current state as reference; i.e. an updated Lagrangian measure.

In order to compare the characteristics of the stress rates, localization of deformation was predicted by using the Truesdell stress rate and the convected stress rate, and the results were compared with those by the Jaumann stress rate of the Cauchy stress. However, in plane strain state, the predicted stresses of incipience of the localization by the Truesdell stress rate become close to the experimental critical stresses, Also, the orientations of the localized deformation obtained by the Truesdell stress rate showed consistency with those by the infinitesimal deformation theory, when the stress levels of the localization were in practical order.

The Jaumann stress rate of the Cauchy stress is usually used to represent hypoelasticity. Since this stress rate takes into account only the effect of finite rotation; i.e. spin during motion, we here examined the effects of deformation rate terms which can be included in the definitions of the stress rates. First we have shown that the Truesdell stress rate can be defined as a rate of the 2nd Piola-Kirchhoff stress with the current state as reference; i.e. an updated Lagrangian measure.

REFERENCES

- 1) Hill, R.: *The Mathematical Theory of Plasticity*, Oxford Classic Texts in the Physical Sciences, Clarendon Press, 1998.
- 2) Hill, R.: Acceleration waves in solids, *J. Mech. Phys. Solids*, Vol.10, pp.1-16, 1962.
- 3) Hill, R. and Hutchinson, J. W.: Bifurcation phenomena in the plane tension test, *J. Mech. Phys. Solids*, Vol.23, pp.239-264, 1975.
- 4) Anand, L. and Spitzig, W. A.: Initiation of localized shear bands in plane strain, *J. Mech. Phys. Solids*, Vol.28, pp.113-128, 1980.
- 5) Asaro, R. J.: Micromechanics of crystals and polycrystals, *Advances in Appl. Mech.*, Vol.23, pp.1-115, 1983.
- 6) Ratel, R., Kawauchi, M., Mori, T., Saiki, I., Withers, P. J. and Iwakuma, T.: Application of anisotropic inclusion theory to the deformation of Ni based single crystal superalloys: Stress-strain curves determination, *Mech. Mater.*, Vol.42, pp.237-247, 2010.
- 7) Rudnicki, J. W. and Rice, J. R.: Conditions for the localization of deformation in pressure-sensitive dilatant materials, *J. Mech. Phys. Solids*, Vol.23, pp.371-394, 1975.
- 8) Nemat-Nasser, S. and Shokooh, A.: On finite plastic flows of compressible materials with internal friction, *Int. J. Solids Structures*, Vol.16, pp.495-514, 1980.
- 9) de Souza Neto, E. A., Perić, D. and Owen, D. R. J.: *Computational Methods for Plasticity: Theory and Application*, John Wiley & Sons, Inc., 2008.

- 10) Lee, E. H., Mallett, R. L. and Wertheimer, T. B.: Stress analysis for anisotropic hardening in finite-deformation plasticity, *J. Appl. Mech.*, Trans. ASME, Vol.50, pp.554-560, 1983.
- 11) Nemat-Nasser, S.: *Plasticity, A Treatise on Finite Deformation of Heterogeneous Inelastic Materials*, Cambridge Monographs on Mechanics, Cambridge Univ. Press, 2005.

Table 1 Material parameters

x	y
a	b
c	d

Table 2 Experimental settings

a b
c d

【図】

Fig. 1 First results




Fig. 2 Second results



Photo 1 My helicopter